



POS Supported Devices

Datasheet



Verifone P400



Verifone V240M



Ingenico Link 2500



Ingenico Lane 3000

	Verifone P400	Verifone V240M	Verifone E285	Ingenico Link 2500	Ingenico Lane 3000
Payment Acceptance Types	EMV, MSR, NFC/CTLS	EMV, MSR, NFC/CTLS	EMV, MSR, NFC/CTLS	EMV, MSR, NFC/CTLS	EMV, MSR, NFC/CTLS
Communications	USB / Ethernet / Wifi 5 GHz + 2.4 GHz	2G / 3G / Bluetooth 4.2 / Wifi	Wifi 5 GHz + 2.4 GHz / USB-C	3G / Wifi 5 GHz + 2.4 GHz / GPRS	Ethernet / Wifi 5 GHz + 2.4 GHz / Bluetooth
Security	PCI PTS 5.x approved	PCI PTS 5.x approved	PCI PTS 5.x approved	PCI PTS 4.x ready	PCI PTS 5.x approved
OS	V/OS (Linux Based)	V/OS (Linux Based)	V/OS (Linux Based)	Telium Tetra	Telium Tetra HTML5
Display	3.5" HVGA	3.5" HVGA	2.8" HGVA	2.4" QVGA	2.8" QVGA
Touchscreen	Capacitive touchscreen	Capacitive touchscreen	—	—	Finger and stylus
Printer	No	30 lps, 40mm paper roll	No	No	No
Memory	1024MB	348MB	512MB Flash, 512MB DDR	256MB Flash, 128MB RAM	256MB Flash, 128MB RAM / Micro SD up to 32GB
Environments	Ideal for Retail and Hospitality	Ideal for Hospitality (PAT)	Ideal for Mobile solutions	Ideal for Mobile solutions	Ideal for Retail and Hospitality

